## CLAIMS

What is claimed is:

A computing system, comprising:


a first approximation apparatus to approximate the term  $2^X$ , wherein X is

- 3 a real number;
- a memory to store a computer program that utilizes the first
- 5 approximation apparatus; and
- a central processing unit (CPU) to execute the computer program, the
- 7 CPU is cooperatively connected to the first approximation apparatus and the
- 8 memory.
- 1 2. The system of claim 1, wherein the first approximation apparatus 2 includes:
- a rounding apparatus to accept an input value (X) that is a real number represented in floating-point format, and to compute a rounded value (LX linteger) by rounding the input value (X) toward minus infinity, wherein the rounded
- 6 value (LX l<sub>integer</sub>) is represented in an integer format.
  - 3. The system of claim 1, wherein the first approximation apparatus includes:
- an integer-to-floating-point converter to accept as input a first rounded
- 4 value ( $[X]_{integer}$ ) represented in an integer format, and to convert the first
- 5 rounded value (LX J<sub>integer</sub>) to a second rounded value (LX J<sub>floating-point</sub>) represented
- 6 in floating-point format.
- 1 4. The system of claim 1, wherein the first approximation apparatus
- 2 includes:

42390P10416

-20-

PAT. APPL.



- 5. The system of claim 1, wherein the first approximation apparatus includes a shift-left logical operator to generate a shifted [X] integer value by shifting a rounded value ([X] integer) to the left by a predetermined number of bit positions.
- The system of claim 1, wherein the first approximation apparatus includes:
   a second approximation apparatus to accept ΔX as input, to approximate
   2<sup>ΔX</sup>, and to return an approximation of 2<sup>ΔX</sup>, wherein ΔX = X [X]<sub>floating-point</sub> and
   [X]<sub>floating-point</sub> is the input value (X) rounded toward minus infinity and is
   represented in floating-point format.
- 7. The system of claim 6, wherein the second approximation apparatus computes the approximation of  $2^{\Delta X}$  by applying Horner's method in calculating a sum of a plurality of elements of a series in the equation  $2^{\Delta X} = \sum_{N=0}^{\infty} \frac{(\Delta X \ln 2)^{N}}{N!}.$
- 1 8. The system of claim 1, wherein the first approximation apparatus includes:
  2 includes:
  3 an integer addition operator to accept a shifted LX integer value and an approximation of  $2^{\Delta X}$  as input, and to perform an integer addition operation on the shifted LX integer value and the approximation of  $2^{\Delta X}$  to generate an approximation of  $2^{X}$ , wherein  $\Delta X = X LX$  floating-point and LX floating-point is the input

42390P10416 -21- PAT. APPL.





1

value (X) rounded toward minus infinity and is represented in floating-point format.

- 9. The system of claim 1, further comprising:
- 2 a third approximation apparatus to approximate a term  $C^Z$ , wherein C is a
- 3 constant and a positive number and Z is a real number,
- 4 the third approximation apparatus using a floating-point multiplication
- operator to compute a product of  $\log_2 C \times Z$ , and feeding the product of  $\log_2 C \times Z$
- 6 Z into the first approximation apparatus to generate an approximation of  $C^{Z}$ .
- 1 10. A method comprising:
- 2 generating a first rounded value and a second rounded value;
- 3 subtracting the second rounded value from an input value (X) to generate
- 4  $\Delta X$ ;
- 5 generating an approximation of  $2^{\Delta X}$ ;
- 6 performing a bit-wise left shift to the first rounded value to generate a
- 7 shifted value; and
- 8 approximating 2<sup>X</sup> by performing an integer addition operation to add the
- 9 shifted value to the approximation of  $2^{\Delta X}$ .
- 1 11. The method of claim 10, wherein generating the first rounded value
- 2 comprises:
- 3 rounding an input value (X) downward to generate the first rounded
- 4 value represented in an integer format.
- 1 12. The method of claim 10, wherein generating the second rounded
- 2 value comprises:

PAT. APPL.



3

4

5

converting the first rounded value represented in an integer format to the second rounded value represented in floating-point format.

- 1 13. The method of claim 10, wherein generating an approximation of
- 2  $2^{\Delta X}$  comprises:
- 3 applying Horner's method in calculating a sum of a plurality of elements
- 4 of a series in the equation  $2^{\Delta X} = \sum_{N=0}^{\infty} \frac{(\Delta X \ln 2)^{\frac{N}{N}}}{N!}$ .
- 1 14. The method of claim 10, wherein performing a bit-wise left shift 2 operation to the first rounded value comprises:
  - shifting the first rounded value to the left by a predetermined number of bit positions so that the first rounded value occupies bit positions reserved for an exponent of a floating-point value.
- 1 15. The method of claim 10, wherein approximating 2<sup>X</sup> comprises:
  2 performing an integer addition operation to add the shifted value to the
  3 approximation of 2<sup>ΔX</sup>, such that the first rounded value is added to an exponent
  4 value of the approximation of 2<sup>ΔX</sup>.
- 1 16. A machine-readable medium comprising instructions which, when 2 executed by a machine, cause the machine to perform operations comprising:
- a first code segment to perform computations to approximate the term 2<sup>X</sup>, wherein X is a real number.
- 1 \_\_\_\_\_\_ The machine-readable medium of claim 16, wherein the first
- 2 approximation apparatus includes:
- 3 a second code-segment to accept an input value (X) that is a real number
- 4 represented in floating-point format, to compute a rounded value  $(X)_{\text{teger}}$  by

42390P10416



1

2

3

4

5

1

2

3

4

5

6

7

1

rounding the input value (X) toward minus infinity, and to return the rounded value ( $[X]_{integer}$ ) which is represented in an integer format.

- 1 18. The machine-readable medium of claim 17, wherein the second code segment computes the approximation of  $2^{\Delta X}$  by applying Horner's method in calculating a sum of a plurality of elements of a series in the following equation,  $2^{\Delta X} = \sum_{N'}^{\infty} \frac{(\Delta X \ln 2)^{\frac{N}{N}}}{N!}$ .
  - 19. The machine-readable medium of claim 16, wherein the first code segment includes:

a third code segment to accept  $\Delta X$  as input and to generate an approximation of  $2^{\Delta X}$ , wherein  $\Delta X = X - \lfloor X \rfloor_{\text{floating-point}}$  and  $\lfloor X \rfloor_{\text{floating-point}}$  is the input value (X) rounded and is represented in floating-point format.

20. The machine-readable medium of claim 16, wherein the first code segment includes:

a fourth code segment to accept a shifted  $\lfloor X \rfloor_{integer}$  value and an approximation of  $2^{\Delta X}$  as input, and to generate an approximation  $2^X$  by performing an integer addition operation on the shifted  $\lfloor X \rfloor_{integer}$  value and the approximation of  $2^{\Delta X}$ , wherein  $\Delta X = X - \lfloor X \rfloor_{floating-point}$  and  $\lfloor X \rfloor_{floating-point}$  is the input value (X) rounded and is represented in floating-point format.

- 21. The machine-readable medium of claim 16, further includes:
- a fifth code segment to approximate a term C<sup>Z</sup>, wherein C is a constant and a positive number and Z is a real number, the fifth code segment computing a product of log<sub>2</sub> C x Z and feeding the product of log<sub>2</sub> C x Z into the first code segment to generate an approximation of C<sup>Z</sup>.

42390P10416